


# PIXEL 240 WHITE




## Product information

Flexible high-power LED strip with white reflective surface and 3M high quality adhesive on the back. The LED strip can be used in any indoor environment to highlight architectural details or integrated into furnitures to add values to any space. An alluminium profile must be used to act as a heatsink.

Watt/Meter	19.2	Voltage	24VDC
Led/Meter	240	SMD LED	3528
Lumen/Meter @3000K	1270	IP	33
CCT	2700K 3000K 4000K	Cut	25 mm
CRI	> 80	Width	10 mm
Life time	> 30.000 h	Ambient temp.	-20°C / +45°C

## Dimensions



## Codes

LED Strip 2700K (5m)	83PIXEL 24024 WP 2700
LED Strip 3000K (5m)	83PIXEL 24024 WP 3000
LED Strip 4000K (5m)	83PIXEL 24024 WP 4000

## Accessories

### Connector With Wire

313CONNEW10



### Description:

Connector with wire for 10 mm white led strip.

### Connector Without Cable


313CONNE10



### Description:

Connector without wire for 10 mm with single color led strip.

## Reel Packaging



### Description:

all the strip led will be delivered in 5m reel packaging.

## Suggested Profiles

Code	PDSA	8545AL	85STE02	85STE06	85STE09	851UNICA	85MICA	85STE01	85STE03	85STE08	85STE10	851UNICAXL
Profiles												
Heat dissipation and/or LED strip width	✓	✓	✗	✓	✗	✗	✗	✓	✗	✓	✓	✗
Dots free with opal diffuser @ max lighting flux	✓	✓	✗	✓	✗	✗	✗	✓	✗	✓	✓	✗



EUROPEAN CONFORMITY



RESTRICTION OF HAZARDOUS SUBSTANCES DIRECTIVE



DIMMABLE

Information provided with this document may be subject to change at any time without notice.

RELEASED ON 03.07.2018