

SNAKE TOP MINI RGB



IP68 FLEXIBLE STRIP LED LIGHT LINE FULLY ENCAPSULATED IN POLYURETHANE COMPOUND. RESISTANT TO WATER, UV RADIATION, ABRASION AND CHEMICALS. VERY BRIGHT AND HOMOGENEOUS ILLUMINATION OVER THE ENTIRE LIGHT EMITTING SURFACE ALSO IN CURVE FORM. CLEAR CURVED OR LINEAR LINES AND LIGHT-EMITTING SURFACE ENABLES A FLUSH INSTALLATION IN CEILINGS, WALLS AND FURNITURE. THE SNAKE ARE PROVIDED WITH 40 CM OF CABLE WITHOUT CONNECTORS FROM BOTH SIDES; THE CABLE FEED ENABLES A SHADOW FREE ALIGNMENT.


TECHNICAL DATA

WATT/METER	10	VOLTAGE	24vdc
LED/METER	98	IP	68
R	620 - 625nm	CUT	62.5mm
G	520 - 525nm	AMBIENT TEMP.	-25°C ~ +65°C
B	460 - 465nm		

CUSTOM: (IT IS POSSIBLE TO REQUEST)


- A SINGLE CABLE EXIT *
- DIFFERENT TYPES OF CABLE EXIT

*WE SUGGEST TO USE 2 CABLE EXITS FOR LENGTHS GREATER THAN 2000mm




DRAWINGS

STANDARD: 2 FRONT CABLE EXIT - 400mm CABLE ON BOTH SIDES



NOTE: THE CUSTOM LENGTHS YOU PROVIDE HAVE TO BE CHECKED AND CONFIRMED BY US IN ORDER TO PROVIDE THE PRODUCT WITHOUT ANY SHADOW AREAS ON THE ENDS


HOW TO BEND



✓ CORRECT

✗ DO NOT BEND THIS WAY

MAX BENDING RADIUS



CODES

SNAKE TOP MINI RGB

83 SNAKETOPMV2 CUSRGB

INDICATE THE DESIRED LENGTH (mm) IN THE REQUEST



DIMMABLE LIGHT



HIGH LIGHT OUTPUT



RESISTANT TO SOLVENTS



UV PROTECTED



TEST REPORT



FC CERTIFIED



ETL CERTIFIED



CE CERTIFIED


ALUMINUM MOUNTING PROFILE

PROFILE MATERIAL: ALUMINUM
STANDARD LENGTH: 1 mt.



CODES

SNAKE TOP MINI MOUNTING PROFILE (1000mm) **85 SNAKETOPMV2 1000AAN**

TECHNICAL DATA





STAINLESS STEEL (SUS201) FLEXIBLE MOUNTING PROFILE



CODES

SNAKE TOP MINI BENDING MOUNTING PROFILE (970mm) **85 SNAKETOPMV2 CUR970SS**

MOUNTING BRACKET



3 STAINLESS STEEL BRACKETS FOR EACH METER OF SNAKE ARE INCLUDED IN THE SHIPMENT, EXTRA BRACKET SET ON REQUEST

CODES

STAINLESS STEEL BRACKETS

85 SNAKESTAF SS TOPMV2

WIRING DIAGRAM

